



2009 KIA SEDONA SPECIFICATIONS

GENERAL INFO	
Body configuration	Minivan
Body type	Steel unibody
Drivetrain layout	Front engine, front-wheel drive
Passenger capacity	7

ENGINE	SWB	LWB
Type	3.8-liter V6, 60-degree six-cylinder, aluminum block and aluminum heads	3.8-liter V6, 60-degree six-cylinder, aluminum block and aluminum heads
Valve gear	Four valves per cylinder, DOHC with CVVT	Four valves per cylinder, DOHC with CVVT
Horsepower (hp @ rpm)	250 @ 6000	250 @ 6000
Torque (lb.-ft @ rpm)	253 @ 3500	253 @ 3500
Bore x stroke (mm)	96.0 x 87.1	96.0 x 87.1
Displacement (cc)	3778	3778
Compression ratio	10.4:1	10.4:1
Emissions rating	50-state LEV-II (ULEV) Tier-2 (Bin 5)	50-state LEV-II (ULEV) Tier-2 (Bin 5)
Fuel tank capacity (gal.)	21.1	21.1
Coolant capacity (qt.)	8.6	8.6
Engine oil capacity (qt.)	5.2	5.2

DRIVETRAIN	
Transmission	Electronically-controlled five-speed automatic, overdrive
Gear ratios :1	
1 st	3.789
2 nd	2.064
3 rd	1.421
4 th	1.034
5 th	0.728
Reverse	3.808
Final drive	3.333

SUSPENSION	
Front	MacPherson struts, coil springs, anti-roll bar
Rear	Multi-link with struts, coil springs

STEERING	SWB	LWB
Type	Power-assisted rack-and-pinion	
Turns, lock-to-lock	3.3	3.5
Turning circle, curb-to-curb (ft.)	38.2	39.6

DIMENSIONS (in.)	SWB	LWB
Exterior:		
Overall length	189.4	202.0
Overall width	78.1	78.1
Overall height	69.3	69.3
Wheelbase	113.8	118.9
Track, front/rear	66.3 / 66.3	66.3 / 66.3
Ground clearance	6.57	6.57
Interior:		
Head room, front/middle/rear	40.9 / 39.8 / 36.4	40.9 / 39.8 / 38.3
Shoulder room, front/middle/rear	63.2 / 65.3 / 57.2	63.2 / 65.3 / 60.5
Leg room, front/middle/rear	41.7 / 37.0 / 33.9	41.7 / 40.9 / 34.0
Hip room, front/middle/rear	59.2 / 65.8 / 49.3	59.2 / 65.9 / 50.1
Interior volume (cu. ft.)	161.6	172.3
Front/middle/rear	63.5 / 56.6 / 41.5	63.5 / 62.5 / 46.3
Cargo volume (cu. ft.)	12.9 / 61.8 / 121.3	32.2 / 80.1 / 141.5
Behind 3 rd row/3 rd row removed/2 nd and 3 rd rows removed		

CURB WEIGHT (lb.)	SWB	LWB
Standard	4365	4387
Full option	4618	4646
Weight distribution (front/rear)	58 / 42	57 / 43

BRAKES	
Type	Four-channel ABS, hydraulic vacuum power-assisted, electronic stability control (ESC), brake-assist, traction control (TCS) and electronic brake-force distribution (EBD)
Front	11.7-inch ventilated discs
Rear	11.9-inch solid discs

TIRES & WHEELS	SWB	LWB
Tires	P225/70R16	P225/70R16 (LX) P235/60R17 (EX)
Wheels	6.5J x 16, steel	6.5J x 16, steel (LX) 6.5J x 17, alloy (EX)

TOWING, GVWR (lb.)	SWB	LWB
Towing capacity (w/o trailer brakes)	--	1000
Towing capacity (w/ trailer brakes)	--	3500
GVWR	5897	5898

FUEL ECONOMY (mpg)	SWB	LWB
		City/Highway
A/T	16 / 23	16 / 23